




TYPICAL APPLICATION:
SECURING PANELS AND RACK
MOUNTED EQUIPMENT



ZINC PLATING ON THIS
PART SERIES IS BEING
PHASED OUT IN FAVOR OF
AN RoHS-COMPLIANT ZINC

©2016 DUPREE, INC.

PART NO. EXAMPLE: **PS 8SM 8 DT S15BG** = PAN-L-SCREW, SHEET METAL, 8-18 X 1/2" LG, STEEL, TORX® RECESS, SEMI-GLOSS BEIGE PER FED-STD-595 NO. 27722

HEAD TYPE	THREAD			RECOMMENDED INSTALLATION HOLE SIZE	L LENGTH							TOL. ±.03	MATERIAL	COLOR CODE	DIM DATA ±.020			
	CODE	NOMINAL DIAMETER	PITCH		1/4	3/8	1/2	5/8	3/4	7/8	1				A	B	D	E
PS	4SM	4	24	.094	4	6	8	10	12			DT STEEL Torx® RECESS	SEE STOCK COLOR LIST Doc No. SCL870115	.312	.117	.037	T10	
	6SM	6	20	.106	4	6	8	10	12	14	16			.375	.137	.040	T15	
	8SM	8	18	.125		6	8	10	12	14	16			.438	.158	.043	T20	
	10SM	10	16	.144		6	8	10	12	14	16			.500	.179	.046	T25	

FEATURES:

- The one piece screw and captive washer simplifies handling, installation and removal of attachment hardware.
- Attachment hardware, color-matched with the mounting surface eliminates distraction from the information display by blending with the background.
- Screw heads are formed by cold forging, followed by a case hardening and heat treating process which increases the basic tensile strength of the material. The resultant high tensile strength thus eliminates burring and yield of the substrate under the coating material.
- The thermosetting coating material used in combination with the relatively hard screw heads is resistant to abrasion and screwdriver damage. This feature virtually eliminates the need for touch-up painting after assembly.
- The nylon washer provides a resilient cushion to protect the finished surface of panels and equipment.
- A self-locking feature to prevent vibration from loosening the screw is achieved by the compression effect of the nylon washer between the screw head and the mounting surface.
- A seal for moisture, low pressure gases and vapors can be affected between the screw head and the mounting surface by the compression of the nylon washer.
- Type 'AB' thread style offers a fine pitch thread with a sharp gimlet point which aides entry of the Pan-L-Screw where hole misalignment could cause problems.

NOTES:

- Torx® is a registered trademark of Camcar Textron.
- The screws listed in this series reflect high quality with emphasis on the forming of the Torx® recess to meet design specification.
- Care should be exercised to assure that the screwdriver tools meet the

- same quality and design specification in order to eliminate mismatching and subsequent damage to the drive recess and coating material.
- The recommended installation hole sizes shown in the table are for light gage (.030) sheet metals. Compensation should be made for other materials and thickness. Refer to ASME B18.6.3, Appendix for details.
- These Pan-L-Screws are capable of forming mating threads in steel plate with a maximum Rockwell hardness of B70-85 without thread shearing or breakage.
- These Pan-L-Screws are primarily intended for application in light sheet metal, plywood, certain plastics or material similar in composition where frequent removal is not necessary. They are not recommended for installation into brittle materials.
- The thread diameters and lengths listed in the table are industry standard sizes. Inventory levels of these sizes may vary at any one time due to customer demands and lead time necessary for production. Lengths not listed are also available on order.
- For color-coated screw less washer, omit the letter P from the head type code.

SPECIFICATIONS:

- Screws are in accordance with ASME Standard No. B18.6.3, Recessed Head Tapping Screws, Type AB, except for recess.
- Screws are stocked zinc plated per ASTM B633, Class SC1, Type II.
- Washer color is achieved by molding with pigmented nylon per ASTM D4066.
- Screw head coating and washer color are matched to customer requirements. We recommend selection from FED-STD-595 whenever possible but we are also prepared to match customer-furnished color chips or samples.

<p>STAKE FASTENER CO. 14395 RAMONA AVENUE CHINO, CALIFORNIA 91710 (909) 597-4889 FAX (909) 597-3043 CAGE 12324 sales@stakefastener.com</p>		<p>PAN-L-SCREW COLORED HEAD, SHEET METAL THREAD, STEEL, TORX® RECESS</p>
---	--	---