



ZINC PLATING ON THIS PART SERIES IS BEING PHASED OUT IN FAVOR OF AN RoHS-COMPLIANT ZINC

STRAIGHT SIDE OR RADIUS PERMISSIBLE

©2016 DUPREE, INC.

PART NO. EXAMPLE: **OHC 8C 10 D S17BL** = 82° OVAL HEAD SCREW .164-32 X 5/8" LG, ALLOY STEEL, PHILLIPS DRIVE, SEMI-GLOSS BLUE PER FED-STD-595 NO. 25488

| HEAD TYPE | THREAD | | L LENGTH | | | | | | | | | MATERIAL | COLOR CODE | DIMENSIONAL DATA | | | |
|-----------|--------|----------------|----------|------|-----|------|-----|-----|-----|-----|----|---------------------------------|---|------------------|--------------|--------|--------|
| | CODE | SIZE | 1/4 | 5/16 | 3/8 | 7/16 | 1/2 | 5/8 | 3/4 | 7/8 | 1 | | | A SHARP | A' ABS. MIN. | H REF. | O MAX. |
| OHC | 4C | .112-40 UNC-2A | 4 | 5 | 6 | 7 | 8 | 10 | 12 | 14 | 16 | D STEEL PHILLIPS DRIVE | SEE STOCK COLOR LIST Doc No. SCL870115 | .225 | .195 | .067 | .104 |
| | 6C | .138-32 UNC-2A | 4 | 5 | 6 | 7 | 8 | 10 | 12 | 14 | 16 | | | .279 | .244 | .083 | .128 |
| | 8C | .164-32 UNC-2A | | 5 | 6 | 7 | 8 | 10 | 12 | 14 | 16 | | | .332 | .292 | .100 | .152 |
| | 10F | .190-32 UNF-2A | | | 6 | 7 | 8 | 10 | 12 | 14 | 16 | | | .385 | .340 | .116 | .176 |

FEATURES:

1. Screws are furnished with pre-colored heads to match panels and equipment. The coating material used in combination with the relatively hard screw heads is resistant to abrasion and screwdriver damage. This feature virtually eliminates the need for touch-up painting after assembly.
2. Screw heads are formed by cold forging which increases the basic tensile strength of the material. The resulting high tensile strength thus eliminates burring and yield of the substrate under the coating material.
3. Screw heads are cleaned and prepared for maximum adhesion of the coating material. The thermosetting coating material is both abrasion and solvent resistant. Slight overspray on underside of head is permissible.

NOTES:

1. The screws listed in this series reflect high quality with emphasis on the forming of the Phillips recess to meet design specification.
2. Care should be exercised to assure that the screwdriver tools meet the same quality and design specification in order to eliminate mismatching and subsequent damage to the drive recess and coating material.
3. The thread diameters and lengths listed in the table are industry standard sizes. Inventory levels of these sizes may vary at any

one time due to customer demands and lead time necessary for production. Lengths not listed are also available on order.

SPECIFICATIONS:

1. Screws are in accordance with ASME Standard No. B18.6.3, Recessed Head Machine Screws.
2. Screws are alloy steel and are stocked zinc plated in accordance with ASTM B633, Class SC1, Type II.
3. Threads are in conformance with H28 Federal Handbook for threads.
4. Coating colors are matched to customer requirements. We recommend selection from FED-STD-595 whenever possible but we are also prepared to match customer-furnished color chips or samples.

STAKE FASTENER CO.

14395 RAMONA AVENUE
CHINO, CALIFORNIA 91710
(909) 597-4889 FAX (909) 597-3043
CAGE 12324 sales@stakefastener.com



COLORED SCREW

COLORED 82° OVAL HEAD,
MACHINE THREAD, ALLOY STEEL,
PLATED