



© 2016 DUPREE, INC.

PART NO. EXAMPLE: **FH 10F 10 D S01YE** = 100° FLAT HEAD SCREW, .190-32 X 5/8" LG, STEEL, PHILLIPS DRIVE, SEMI-GLOSS YELLOW PER FED-STD-595 NO. 26555

HEAD TYPE	THREAD		L LENGTH								MATERIAL	COLOR CODE	DIMENSIONAL DATA				
	CODE	SIZE	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8			1	A SHARP	A' ABS. MIN.	B	C
FH	4C	.112-40 UNJC-3A	4	5	6	7	8	10	12	14	16	D STEEL PHILLIPS DRIVE	SEE STOCK COLOR LIST Doc No. SCL870115	.225	.183	.045	.012
	6C	.138-32 UNJC-3A	4	5	6	7	8	10	12	14	16			.279	.233	.057	.014
	8C	.164-32 UNJC-3A	4	5	6	7	8	10	12	14	16			.332	.282	.068	.015
	10F	.190-32 UNJF-3A	4	5	6	7	8	10	12	14	16			.385	.332	.080	.016

**FEATURES:**

1. Screws are furnished with pre-colored heads to match panels and equipment. The coating material used in combination with the relatively hard screw heads is resistant to abrasion and screwdriver damage. This feature virtually eliminates the need for touch-up painting after assembly.
2. Screw heads are formed by cold forging, followed by a heat treating process which increases the basic tensile strength of the material. The resultant high tensile strength thus eliminates burring and yield of the substrate under the coating material.
3. Screw heads are cleaned and prepared for maximum adhesion of the coating material. The thermosetting coating material is both abrasion and solvent resistant. Slight overspray on underside of head is permissible.

**NOTES:**

1. The screws listed in this series reflect aircraft quality with emphasis on the forming of the Phillips recess to meet design specification.

2. Care should be exercised to assure that the screwdriver tools meet the same quality and design specification in order to eliminate mismatching and subsequent damage to the drive recess and coating material.
3. The thread diameters and lengths listed in the table are industry standard sizes. Inventory levels of these sizes may vary at any one time due to customer demands and lead time necessary for production. Lengths not listed are also available on order.

**SPECIFICATIONS:**

1. Screws meet all requirements of NAS514. Screws are stocked cadmium plated per QQ-P-416, Type II, Class 2.
2. Threads are in conformance with MIL-S-8879 and H28 Federal Handbook for threads.
3. Coating colors are matched to customer requirements. We recommend selection from FED-STD-595 whenever possible but we are also prepared to match customer-furnished color chips or samples.

**STAKE FASTENER CO.**

14395 RAMONA AVENUE  
CHINO, CALIFORNIA 91710  
(909) 597-4889 FAX (909) 597-3043  
CAGE 12324 sales@stakefastener.com



**COLORED SCREW**

100° FLAT HEAD,  
MACHINE THREAD, ALLOY STEEL,  
PLATED